

# PowerWalker VI 750T/HID

Line-Interactive UPS

750VA Line-Interactive UPS with pure Sine Wave

4 IEC Outlets, Phone/Network surge protection with TVSS


USB Connection for monitoring, HID compatible

LCD display for status view

Built-in boost and buck AVR function




Item-No. 10121007



## Product Features

PowerWalker VI 750T/HID is a Line-Interactive UPS with pure sine wave output and designed for fulfilling high quality power protection demand. It offers a pure sine wave output for smooth operation even in battery mode. A HID compatible USB port allows monitoring basic UPS status on Windows, Mac OS, Linux systems without installing additional software. HID Power Devices are supported by computer OS's internal power management originally. This also makes this model best choice for all equipment that is not suitable for installing monitoring software but supports USB-HID like NAS, HID compatible surveillance video recording systems, ATM etc. With its compact foot print PowerWalker VI750T/HID fits easily into small spaces such as ATM, Kiosks, narrow industrial and office applications.

- Pure sine wave output for smooth operation in battery mode
- Monitoring software included
- HID-compliant USB port
- High conversion efficiency results in energy saving
- Equipped with Boost and Buck AVR to stabilize output voltage
- 50/60 Hz frequency input (auto sensing)
- Auto restart while AC recovery
- Self-Monitoring and Fault Diagnosis
- Easy, user replaceable, battery design
- Optional: MBS, ATS



Backside:  
USB, 4x IEC outlets,  
RJ45 surge protection,

Backup time  
(Half SPS Load)  
9 min

More details  
will follow

## Technical Details

### Product Features

<b>Capacity</b>	750VA/500W
-----------------	------------

### Input

<b>Voltage</b>	220/230/240VAC
<b>Input Voltage Range</b>	184-276VAC (AVR Range for 230V)
<b>Frequency Range</b>	50/60Hz $\pm$ 5Hz% for normal mode, autosensing

### Output

<b>Voltage</b>	220/230/240VAC
<b>Voltage Regulation</b>	- 10%/+6% of nominal voltage range (Line mode)
<b>Frequency</b>	50 or 60Hz depending on input frequency
<b>Waveform</b>	Pure Sine Wave

### Overload Rating

<b>Line Mode</b>	105% - 120% shutdown after 5min 120% - 150% shutdown after 10s $\geq$ 150% shutdown after 1s
<b>Battery Mode</b>	105% - 110% shutdown after 10s $\geq$ 110% shutdown after 1s

### Transfer Time

<b>Typical</b>	3-7ms Typical, 10ms max;
----------------	--------------------------

### Battery

<b>Type</b>	12V / 9Ah
<b>Quantity</b>	1
<b>Recharge Time</b>	3h to 90% after discharged

### LCD Display

<b>Indicators</b>	AC mode, AVR, Battery mode, Fault alarm, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Low battery alarm
-------------------	---

### Audio Indicators

- Back up mode	Sounding every 10 seconds
- Battery low	Sounding every 3 seconds
- Overload	Sounding every 3 seconds
- Charge fault	Sounding every 1 second
- AVR fault	Sounding every 1 second
- Battery fault	Sounding every 1 second

### Connections

<b>Connection</b>	USB (HID compliant)
<b>Outlets</b>	4x IEC
<b>Surge Protection</b>	RJ45 (in/out)

### Software & System Requirements

<b>Software</b>	WinPower
<b>Operating System</b>	For details visit: <a href="http://www.powerwalker.com/winpower.html">http://www.powerwalker.com/winpower.html</a>

### Product Details

<b>Dimensions (LxWxH)</b>	240 x 150 x 209 mm
<b>Colour</b>	Black
<b>Weight</b>	6.8g
<b>Fan Control</b>	No fan
<b>Noise Level</b>	< 40dB
<b>Model Code</b>	VI 750T/HID

### Environment

<b>Temperature</b>	0°C – 40°C
<b>Humidity</b>	0 - 90% (non-condensing)

### Package Content

<b>Package Content</b>	PowerWalker VI 750T/HID, Input Power Cord, 1x IEC cable, USB cable, Software CD, Manual
------------------------	---

### Optional Accessories

See next page

### Logistic Data

<b>Giftbox Language</b>	EN/DE/FR/PL/IT/ES/SE/RU/FI/BG/CZ/UA/NO/PT/KZ/HR/BY/TR/HU/RS
<b>Manual Language</b>	EN
<b>Dimension/Giftbox</b>	301 x 199 x 295 mm
<b>Weight/Giftbox</b>	7.8 kg
<b>Pieces/carton</b>	1
<b>Pieces/pallet</b>	tbc
<b>BlueWalker Item-No.</b>	10121007
<b>EAN</b>	4260074976632
<b>Warranty</b>	24 Months (except battery)

See UPS configurator on [www.powerwalker.com](http://www.powerwalker.com) for detailed backup time information.

## Optional Accessories



IEC -> Schuko Converter  
Item Nr.: 91015003



1x Yuasa 12V/9Ah battery  
Datasheet: [Link](#)  
CSB or Panasonic brand can also be used



MBS (Maintenance Bypass Switch)  
Datasheet: [Link](#)  
Item No.: 10120500