

Certificate

Issue Date: January 16, 2020
Ref. Report No. ISL-20LE044CE

Product Name : Network Attached Storage
Model(s) : AS7110T; ASXXXXXXXXXX; DSXXXXXXXXXX; NVRXXXXXXXXXX;
NNRXXXXXXXXXX; MXXXXXXXXXX; NRXXXXXXXXXX; VXXXXXXXXXX;
ANXXXXXXXXXX; FSXXXXXXXXXX; YSXXXXXXXXXX; ZSXXXXXXXXXX;
LOXXXXXXXXXXXXXXXXXX
(where "X" may be 0-9, A-Z, a-z, "+", "-" or blank for marketing purpose, no
impact for safety related constructions and critical components.)
Responsible Party : ASUSTOR Inc.
Address : 3F, No. 136, Daye Rd., Beitou Dist., Taipei City 112, Taiwan.

We, **International Standards Laboratory Corp.**, hereby certify that:

The sample ISL received which bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in European Council Directive EMC Directive 2014/30/EU. And Our laboratories is the accredited laboratories and are approved according to ISO/IEC 17025. The device was passed the test performed according to :



Standards:

EN 55032:2015+AC:2016, CISPR 32: 2015+COR1:2016: Class A
AS/NZS CISPR 32:2015: Class A
EN 61000-3-2:2014 and IEC 61000-3-2:2014
EN 61000-3-3: 2013 and IEC 61000-3-3: 2013
EN 55024: 2010+A1:2015 and CISPR 24: 2010+A1:2015
EN 61000-4-2: 2009 and IEC 61000-4-2: 2008
EN 61000-4-3: 2006+A1: 2008 +A2: 2010 and
IEC 61000-4-3:2006+A1: 2007+A2: 2010
EN 61000-4-4:2012 and IEC 61000-4-4:2012
EN 61000-4-5: 2014+A1:2017 and IEC 61000-4-5: 2014+A1:2017
EN 61000-4-6:2014+AC:2015 and IEC 61000-4-6:2013
EN 61000-4-8: 2010 and IEC 61000-4-8: 2009
EN 61000-4-11: 2004+A1:2017 and IEC 61000-4-11: 2004+A1:2017

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The determination of the test results is determined by customer agreement, regulations or standard document specifications.

The Laboratory evaluates measurement inaccuracies based on regulatory or standard document specifications and is listed in the report for reference. The quantitative project part judges the conformity of the test results based on the evaluation results of the standard cited uncertainty, and the qualitative project does not temporarily evaluate the measurement uncertainty.

Angus Chu

Angus Chu / Director



International Standards Laboratory Corp.

☐ **LT LAB:**

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan
Tel: 886-3-407-1718; Fax: 886-3-407-1738

CE MARK TECHNICAL FILE

AS/NZS EMC CONSTRUCTION FILE

of

Product Name

Network Attached Storage

Model

**AS7110T; ASXXXXXXXXXX; DSXXXXXXXXXX;
NVRXXXXXXXXXX; NNRXXXXXXXXXX; MXXXXXXXXXX;
NRXXXXXXXXXX; VXXXXXXXXXX; ANXXXXXXXXXX;
FSXXXXXXXXXX; YSXXXXXXXXXX; ZSXXXXXXXXXX;
LOXXXXXXXXXXXXXXXXXX**

**(where "X" may be 0-9, A-Z, a-z, "+", "-" or blank for
marketing purpose, no impact for safety related
constructions and critical components.)**

Contains:

1. Declaration of Conformity
2. EN 55032/CISPR 32, AS/NZS CISPR 32 EMI test report
3. EN 55024/CISPR 24, EN 61000-3-2 / IEC 61000-3-2, and EN 61000-3-3 / IEC 61000-3-3 test report
4. Block Diagram and Schematics
5. Users' manual

Declaration of Conformity

Name of Responsible Party: ASUSTOR Inc.

Address of Responsible Party: 3F, No. 136, Daye Rd., Beitou Dist.,
Taipei City 112, Taiwan.

Declares that product: Network Attached Storage

Model: AS7110T; ASXXXXXXXXXX; DSXXXXXXXXXX;
NVRXXXXXXXXXX; NNRXXXXXXXXXX;
MXXXXXXXXXXX; NRXXXXXXXXXX;
VAXXXXXXXXXX; ANXXXXXXXXXX;
FSXXXXXXXXXX; YSXXXXXXXXXX;
ZSXXXXXXXXXX; LOXXXXXXXXXXXXXXXXXX
(where "X" may be 0-9, A-Z, a-z, "+", "-" or blank for
marketing purpose, no impact for safety related
constructions and critical components.)

Assembled by: Same as above

Address: Same as above

Conforms to the EMC Directive 2014/30/EU as attested by conformity with the
following harmonized standards:

EN 55032:2015+AC:2016, CISPR 32: 2015+COR1:2016: Class A:
Electromagnetic compatibility of multimedia equipment - Emission requirements.
AS/NZS CISPR 32:2015: Class A: Electromagnetic compatibility of multimedia
equipment- Emission requirements

Performed Item	Test Performed	Deviation	Result
Conducted emissions from the AC mains power ports	Yes	No	PASS
Telecommunication Port Conducted Emissions (asymmetric mode)	Yes	No	PASS
Radiated emissions at frequencies below 1 GHz	Yes	No	PASS
Radiated emissions at frequencies above 1 GHz	Yes	No	PASS
Radiated emissions from FM receivers	N/A	N/A	N/A
Voltage Disturbance Emissions at Antenna Terminals	N/A	N/A	N/A
Differential voltage emissions	N/A	N/A	N/A
Outdoor units of home satellite receiving systems	N/A	N/A	N/A

<to be continued>

EN 55024:2010+A1:2015 and CISPR 24:2010+A1:2015: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4:2012 IEC 61000-4-4:2012	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5:2014+A1:2017 IEC 61000-4-5:2014+A1:2017	Surge	Pass	B
EN 61000-4-6:2014+AC:2015 IEC 61000-4-6:2013	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11:2004+A1:2017 IEC 61000-4-11:2004+A1:2017	Voltage Dips / Short Interruption and Voltage Variation		
	>95% in 0.5 period	Pass	B
	30% in 25 period	Pass	C
	>95% in 250 period	Pass	C

Standard	Description	Results
EN 61000-3-2:2014 IEC 61000-3-2:2014	Limits for harmonics current emissions	Pass
EN 61000-3-3:2013 IEC 61000-3-3:2013	Limits for voltage fluctuations and flicker in low-voltage supply systems.	Pass

We, ASUSTOR Inc., hereby declare that the equipment bearing the trade name and model number specified above was tested conforming to the applicable Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the requirements.

ASUSTOR Inc.

Date: January 16, 2020

Remarks: 1) The responsible party for Declaration of Conformity must be located within Europe, 2) The above is a sample of DoC, one should modify it to meet remark 1.

Declaration of Conformity

Name of Responsible Party: ASUSTOR Inc.

Address of Responsible Party: 3F, No. 136, Daye Rd., Beitou Dist.,
Taipei City 112, Taiwan.

Declares that product: Network Attached Storage

Model: AS7110T; ASXXXXXXXXXX; DSXXXXXXXXXX;
NVRXXXXXXXXXX; NNRXXXXXXXXXX;
MXXXXXXXXXXX; NRXXXXXXXXXX;
VAXXXXXXXXXX; ANXXXXXXXXXX;
FSXXXXXXXXXX; YSXXXXXXXXXX;
ZSXXXXXXXXXX; LOXXXXXXXXXXXXXXXXXX
(where "X" may be 0-9, A-Z, a-z, "+", "-" or blank for
marketing purpose, no impact for safety related
constructions and critical components.)

Assembled by: Same as above

Address: Same as above

Conforms to the EMI part of RCM Mark requirements as attested by conformity with
the following standards:

AS/NZS CISPR 32:2015: Class A: Electromagnetic compatibility of multimedia equipment- Emission
requirements

*We, ASUSTOR Inc., hereby declare that the equipment bearing the trade name and model
number specified above was tested conforming to the applicable Rules under the most
accurate measurement standards possible, and that all the necessary steps have been taken
and are in force to assure that production units of the same equipment will continue to
comply with the requirements.*

ASUSTOR Inc.

Date: January 16, 2020

CE TEST REPORT

of
EN 55032 / CISPR 32 / AS/NZS CISPR 32
Class A
EN 55024 / CISPR 24 / IMMUNITY
EN 61000-3-2 / EN 61000-3-3

Product : **Network Attached Storage**

Model(s): **AS7110T; ASXXXXXXXXXX; DSXXXXXXXXXX;
NVRXXXXXXXXXX; NNRXXXXXXXXXX;
MXXXXXXXXXX; NRXXXXXXXXXX;
VAXXXXXXXXXX; ANXXXXXXXXXX;
FSXXXXXXXXXX; YSXXXXXXXXXX;
ZSXXXXXXXXXX;
LOXXXXXXXXXXXXXXXXXX**
(where "X" may be 0-9, A-Z, a-z, "+", "-" or
blank for marketing purpose, no impact for
safety related constructions and critical
components.)

Applicant: **ASUSTOR Inc.**

Address: **3F, No. 136, Daye Rd., Beitou Dist.,
Taipei City 112, Taiwan.**

Test Performed by:

International Standards Laboratory Corp.

<LT LAB>

*Address:

No. 120, Lane 180, Hsin Ho Rd.,
Lung-Tan Dist., Tao Yuan City 325, Taiwan
*Tel: 886-3-407-1718; Fax: 886-3-407-1738

Report No.: **ISL-20LE044CE**

Issue Date : **January 16, 2020**

This report totally contains 80 pages including this cover page and contents page.

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

Contents of Report

1.	General.....	1
1.1	Certification of Accuracy of Test Data	1
1.2	Test Standards	2
1.3	Description of EUT	5
1.4	Description of Support Equipment	8
1.5	Software for Controlling Support Unit.....	8
1.6	I/O Cable Condition of EUT and Support Units	8
2.	Power Main Port Conducted Emissions	9
2.1	Test Setup and Procedure	9
2.2	Conduction Test Data: Configuration 1	11
2.3	Test Setup Photo.....	13
3.	Telecommunication Port Conducted Emissions	15
3.1	Test Setup and Procedure	15
3.2	Test Data: LAN10G\100M.....	17
3.3	Test Data: LAN10G\10G.....	18
3.4	Test Data: LAN10G\1G.....	19
3.5	Test Data: LAN10G\2.5G Current	20
3.6	Test Data: LAN10G\2.5G Voltage.....	21
3.7	Test Data: LAN1 2.5G\100M.....	22
3.8	Test Data: LAN1 2.5G\1G.....	23
3.9	Test Data: LAN1 2.5G\2.5G Current	24
3.10	Test Data: LAN1 2.5G\2.5G Voltage.....	25
3.11	Test Data: LAN2 2.5G\100M.....	26
3.12	Test Data: LAN2 2.5G\1G	27
3.13	Test Data: LAN2 2.5G\2.5G Current.....	28
3.14	Test Data: LAN2 2.5G\2.5G Voltage.....	29
3.15	Test Data: LAN3 2.5G\100M.....	30
3.16	Test Data: LAN3 2.5G\1G	31
3.17	Test Data: LAN3 2.5G\2.5G Current.....	32
3.18	Test Data: LAN3 2.5G\2.5G Voltage.....	33
3.19	Test Setup Photo	34
4.	Radiated Disturbance Emissions	35
4.1	Test Setup and Procedure	35
4.2	Limit	37
4.3	Radiation Test Data: Configuration 1.....	39
4.4	Test Setup Photo.....	43
5.	Voltage Disturbance Emissions at Antenna Terminals	45
5.1	Test Setup and Procedure	45
6.	Differential Voltage Emissions.....	47
6.1	Test Setup and Procedure	47
7.	Outdoor units of home satellite receiving systems	49
7.1	Test Setup and Procedure	49
8.	Electrostatic discharge (ESD) immunity	51
8.1	Test Specification and Setup	51
8.2	Test Point.....	52
8.3	Test Setup Photo.....	53

9.	Radio-Frequency, Electromagnetic Field immunity	54
9.1	Test Specification and Setup	54
9.2	Test Setup Photo	55
10.	Electrical Fast transients/burst immunity	56
10.1	Test Specification and Setup	56
10.2	Test Setup Photo	58
11.	Surge Immunity	59
11.1	Test Specification and Setup	59
11.2	Test Setup Photo	60
12.	Immunity to Conductive Disturbance	61
12.1	Test Specification and Setup	61
12.2	Test Setup Photo	62
13.	Power Frequency Magnetic Field immunity	63
13.1	Test Specification and Setup	63
13.2	Test Setup Photo	64
14.	Voltage Dips, Short Interruption and Voltage Variation immunity	65
14.1	Test Specification and Setup	65
14.2	Test Setup Photo	66
15.	Harmonics	67
15.1	Test Specification and Setup	67
16.	Voltage Fluctuations	69
16.1	Test Specification and Setup	69
16.2	Test Data	70
16.3	Test Setup Photo	71
17.	Appendix	72
17.1	Appendix A: Test Equipment	72
17.2	Appendix B: Uncertainty of Measurement	75
17.3	Appendix C: Photographs of EUT Please refer to the File of ISL-20LE044P	77

1. General

1.1 Certification of Accuracy of Test Data

Standards: Please refer to 1.2

Equipment Tested: Network Attached Storage

Model: AS7110T; ASXXXXXXXXXX; DSXXXXXXXXXX;
NVRXXXXXXXXXX; NNRXXXXXXXXXX;
MXXXXXXXXXX; NRXXXXXXXXXX; VXXXXXXXXXX;
ANXXXXXXXXXX; FSXXXXXXXXXX; YSXXXXXXXXXX;
ZSXXXXXXXXXX; LOXXXXXXXXXXXXXXXXXX
(where "X" may be 0-9, A-Z, a-z, "+", "-" or blank for marketing purpose, no impact for safety related constructions and critical components.)

Applicant: ASUSTOR Inc.

Sample received Date: December 19, 2019

Final test Date: EMI: refer to the date of test data
EMS: January 13, 2020

Test Site: Chamber 02; Chamber 14; Conduction 02; Immunity 02

Test Distance: 10M; 3M (above 1GHz) (EMI test)

Temperature: refer to each site test data


Humidity: refer to each site test data


Atmospheric Pressure: 86 kPa to 106 kPa

Input power: Conduction input power: AC 230 V / 50 Hz
Radiation input power: AC 230 V / 50 Hz
Immunity input power: AC 230 V / 50 Hz

Test Result: PASS

Report Engineer: Cheryl Tung

Test Engineer:

Stanley Tsai

Approved By:

Benson Chen / Associate Director

1.2 Test Standards

The tests which this report describes were conducted by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp. in accordance with the following

EN 55032:2015+AC:2016, CISPR 32: 2015+COR1:2016: Class A: Electromagnetic compatibility of multimedia equipment - Emission requirements.

AS/NZS CISPR 32:2015: Class A: Electromagnetic compatibility of multimedia equipment- Emission requirements

Performed Item	Test Performed	Deviation	Result
Conducted emissions from the AC mains power ports	Yes	No	PASS
Telecommunication Port Conducted Emissions (asymmetric mode)	Yes	No	PASS
Radiated emissions at frequencies below 1 GHz	Yes	No	PASS
Radiated emissions at frequencies above 1 GHz	Yes	No	PASS
Radiated emissions from FM receivers	N/A	N/A	N/A
Voltage Disturbance Emissions at Antenna Terminals	N/A	N/A	N/A
Differential voltage emissions	N/A	N/A	N/A
Outdoor units of home satellite receiving systems	N/A	N/A	N/A

EN 55024:2010+A1:2015 and CISPR 24:2010+A1:2015: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4:2012 IEC 61000-4-4:2012	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5:2014+A1:2017 IEC 61000-4-5:2014+A1:2017	Surge	Pass	B
EN 61000-4-6:2014+AC:2015 IEC 61000-4-6:2013	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11:2004+A1:2017 IEC 61000-4-11:2004+A1:2017	Voltage Dips / Short Interruption and Voltage Variation		
	>95% in 0.5 period	Pass	B
	30% in 25 period	Pass	C
	>95% in 250 period	Pass	C

Standard	Description	Results
EN 61000-3-2:2014 IEC 61000-3-2:2014	Limits for harmonics current emissions	Pass
EN 61000-3-3:2013 IEC 61000-3-3:2013	Limits for voltage fluctuations and flicker in low-voltage supply systems.	Pass

1.2.1 Performance Criteria for Compliance: EN 55024

Performance criterion A

During and after the test the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a minimum performance level specified by the manufacturer when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion B

After the test, the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion C

During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.

Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

1.3 Description of EUT

EUT

Description:	Network Attached Storage
Condition	Pre-Production
Model:	AS7110T; ASXXXXXXXX; DSXXXXXXXX; NVRXXXXXXXX; NNRXXXXXXXX; MXXXXXXXX; NRXXXXXXXX; VXXXXXXXX; ANXXXXXXXX; FSXXXXXXXX; YSXXXXXXXX; ZSXXXXXXXX; LOXXXXXXXXXXXXXXXX (where "X" may be 0-9, A-Z, a-z, "+", "-" or blank for marketing purpose, no impact for safety related constructions and critical components.)
Serial Number	N/A
Maximum Operating Frequency	3.4GHz

The devices can be installed inside the EUT are listed below:

Component	Vendor	Description
CPU	Intel	Xeon 2224 3.4GHz up to 4.6GHz
Motherboard	Asustor	AS71XXT
USB Flash	ADATA	IUM01-512MFHL
SATA board	Asustor	AS6510T
Memory	DSL	DDR4 2666 16GB CL 19 ECC
M.2 board	Asustor	AS6510T
F-CTRL board	Asustor	AS-6XXT
F-IO board	Asustor	AS-304T
Power Supply	DELTA	DPS-350AB-24 XX (X = 0-9, A-Z or blank)

The I/O ports of EUT are listed below:

I/O Port Type	Quantity
AC-In Connector	1
RJ45 Port (100Mbps/1Gbps/2.5G/10Gbps)	1
RJ45 Port (100Mbps/1Gbps/2.5Gbps)	3
USB 3.0 Port	3

Test Configuration

Configuration	1
CPU	Intel Xeon 2224 3.4GHz up to 4.6GHz
Motherboard	Asustor AS71XXT
USB Flash	ADATA IUM01-512MFHL
SATA board	Asustor AS6510T
Memory	DSL DDR4 2666 16GB CL 19 ECC*2
M.2 board	Asustor AS6510T
F-CTRL board	Asustor AS-6XXT
F-IO board	Asustor AS-304T
Power Supply	DELTA DPS-350AB-24 F
3.5" SATA HDD	WD WD2002FFSX*6 WD WD5000AAKX*4

Different Model list:

Model	Market
AS7110T; ASXXXXXXXX; DSXXXXXXXX; NVRXXXXXXXX; NNRXXXXXXXX; MXXXXXXXX; NRXXXXXXXX; VXXXXXXXX; ANXXXXXXXX; FSXXXXXXXX; YSXXXXXXXX; ZSXXXXXXXX; LOXXXXXXXXXXXXXXXXX (where "X" may be 0-9, A-Z, a-z, "+", "-" or blank for marketing purpose, no impact for safety related constructions and critical components.)	Different customer

EMI Noise Source:

refer to the photo	SATA Crystal
EUT-8	20MHz (X1)
EUT-9	20MHz (X2)
EUT-10	20MHz (X3)
EUT-11	20MHz (X4)
refer to the photo	USB Flash Crystal
EUT-18	12MHz (Y1)
refer to the photo	F-CTRL Crystal
EUT-21	32.768KHz (X1)
refer to the photo	Motherboard Crystal
EUT-27	50MHz (X1)
EUT-28	50MHz (X2)
EUT-29	50MHz (X3)
EUT-30	50MHz (X4)
EUT-31	32.768KHz (X5)
EUT-32	27MHz (X6)
EUT-33	48MHz (X7)
EUT-34	24MHz (X8)

EMI Solution:

refer to the photo	Solution	SPEC (L*W*H) (mm)	Brand	Location
EUT-35	Gasket	40mm*4mm*2mm	Rui Xing	1
	Gasket	40mm*4mm*2mm	Rui Xing	2

1.4 Description of Support Equipment

Unit	Model Serial No.	Brand	Power Cord	FCC ID
Personal Computer*4	RW7 S/N: N/A	Lenovo	Non-shielded, Detachable	FCC DOC
USB3.0 External HDD Enclosure*3 (For EMI Test)	SK2-U31AS-AKT S/N: N/A	AKiTI	N/A	FCC DOC
USB3.0 External HDD Enclosure*3 (For EMS Test)	TS16GJF700 S/N: N/A	Transcend	N/A	FCC DOC
3.5" Hard Disk*6	WD2002FFSX S/N: N/A	WD	N/A	FCC DOC
3.5" Hard Disk*4	WD5000AAKX S/N: N/A	WD	N/A	FCC DOC

1.5 Software for Controlling Support Unit

Test programs exercising various part of EUT were used. The programs were executed as follows:

- A. Search External HDD from EUT RJ45 port with Finder.exe.
- B. Used ping.exe & Tfggen.exe to send signal to EUT RJ45 port through Personal Computer RJ45 Port.
- C. Read and write to the disk drives.
- D. Read and write data in the USB3.0 Hard Disk through EUT USB3.0 port.
- E. Repeat the above steps.

	Filename	Issued Date
USB3.0 External HDD Enclosure	Intel EMC.exe	9/04/2000
RJ45	ping.exe	
RJ45	Tfggen.exe	06/23/1999
EUT	ControlCenter.exe	11/15/2008
3.5" Hard Disk	Intel EMC.exe	9/04/2000


1.6 I/O Cable Condition of EUT and Support Units

Description	Path	Length	Shielding	Core	Remark
AC Power Cord	230V to EUT SPS	1.8m	No	No	
USB3.0 Cable*3	USB3.0 External HDD Enclosure USB 3.0 Port to EUT USB 3.0 Port	1.2m	Yes	No	
RJ45 data Cable	Personal Computer RJ45 Port to EUT RJ45 Port	10m	No	No	Cat 6a
RJ45 data Cable*3	Personal Computer RJ45 Port to EUT RJ45 Port	10m	No	No	Cat 5e

2. Power Main Port Conducted Emissions

2.1 Test Setup and Procedure

2.1.1 Test Setup



2.1.2 Test Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, live and neutral, were measured. All of the interface cables were manipulated according to EN 55032 requirements.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

2.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150kHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9kHz

2.1.4 Limit

Conducted emissions from the AC mains power ports of Class_A equipment:


Frequency	QP	AV
MHz	dB(μ V)	dB(μ V)
0.15-0.50	79	66
0.50-30	73	60
Note: The lower limit shall apply at the transition frequencies		

Conducted emissions from the AC mains power ports of Class_B equipment:

Frequency	QP	AV
MHz	dB(μ V)	dB(μ V)
0.15-0.50	66-56	56-46
0.50-5.0	56	46
5.0-30	60	50
Note: The lower limit shall apply at the transition frequencies		

2.2 Conduction Test Data: Configuration 1

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.154	42.98	28.61	9.69	52.67	79.00	-26.33	38.30	66.00	-27.70
2	0.162	39.39	19.79	9.69	49.08	79.00	-29.92	29.48	66.00	-36.52
3	0.170	37.57	19.38	9.69	47.26	79.00	-31.74	29.07	66.00	-36.93
4	0.178	36.65	15.97	9.68	46.33	79.00	-32.67	25.65	66.00	-40.35
5	0.210	34.44	21.44	9.68	44.12	79.00	-34.88	31.12	66.00	-34.88
6	11.894	23.90	17.65	9.94	33.84	73.00	-39.16	27.59	60.00	-32.41
7	16.178	33.72	31.65	9.97	43.69	73.00	-29.31	41.62	60.00	-18.38

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor


Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.150	44.93	31.45	9.68	54.61	79.00	-24.39	41.13	66.00	-24.87
2	0.182	35.34	15.41	9.68	45.02	79.00	-33.98	25.09	66.00	-40.91
3	0.202	33.94	17.89	9.68	43.62	79.00	-35.38	27.57	66.00	-38.43
4	10.894	31.02	28.76	9.96	40.98	73.00	-32.02	38.72	60.00	-21.28
5	11.554	29.83	25.37	9.97	39.80	73.00	-33.20	35.34	60.00	-24.66
6	12.546	31.63	27.61	9.99	41.62	73.00	-31.38	37.60	60.00	-22.40
7	13.206	32.08	29.51	9.99	42.07	73.00	-30.93	39.50	60.00	-20.50
8	15.518	31.46	28.58	10.02	41.48	73.00	-31.52	38.60	60.00	-21.40
9	16.174	35.73	33.47	10.04	45.77	73.00	-27.23	43.51	60.00	-16.49

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.


If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.3 Test Setup Photo

Front View



Back View



3.1 Test Setup and Procedure

The diagram illustrates a test setup for measuring the common mode impedance of a power supply unit (PSU) and its associated equipment under test (EUT/AE). The setup is mounted on a table with a height of 0.8 m. The PSU and EUT/AE are placed on the table, with the PSU having a height of 0.1 m and the EUT/AE having a height of 0.1 m. The distance between the PSU and EUT/AE is 0.3 m. A current probe is connected to the PSU, with a distance of 0.1 m from the PSU and 0.8 m from the EUT/AE. A cable to the AE is connected to the current probe, with a distance of 0.8 m from the PSU and 0.8 m from the EUT/AE. A cable to the AE is also connected to the EUT/AE, with a distance of 0.8 m from the EUT/AE. The setup is grounded to a vertical reference ground plane, with a distance of 0.4 m from the ground plane to the PSU and 0.4 m from the ground plane to the EUT/AE. The setup is also grounded to a reference ground plane, with a distance of 0.4 m from the reference ground plane to the PSU and 0.4 m from the reference ground plane to the EUT/AE. The setup is also grounded to a reference ground plane, with a distance of 0.4 m from the reference ground plane to the PSU and 0.4 m from the reference ground plane to the EUT/AE.

Frequency Range: 150kHz--30MHz
 Detector Function: Quasi-Peak / Average Mode
 Resolution Bandwidth: 9kHz

3.1.4 Limit

Asymmetric mode conducted emissions from Class_A equipment:

Applicable to

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. antenna ports.

Frequency range MHz	Coupling device	Detector type / bandwidth	Class_A voltage limits dB(μV)	Class_A current limits dB(μA)
0.15-0.5	AAN	Quasi Peak / 9 kHz	97-87	n/a
0.5-30			87	
0.15-0.5	AAN	Average / 9 kHz	84-74	
0.5-30			74	
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	97-87	53-43
0.5-30			87	43
0.15-0.5	CVP and current probe	Average / 9 kHz	84-74	40-30
0.5-30			74	30
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	53-43
0.5-30				43
0.15-0.5	Current Probe	Average / 9 kHz		40-30
0.5-30				30


Asymmetric mode conducted emissions from Class_B equipment:

Applicable to:

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. broadcast receiver tuner ports.
4. antenna ports.

Frequency range MHz	Coupling device	Detector type / bandwidth	Class_B voltage limits dB(μV)	Class_B current limits dB(μA)
0.15-0.5	AAN	Quasi Peak / 9 kHz	84-74	n/a
0.5-30			74	
0.15-0.5	AAN	Average / 9 kHz	74-64	
0.5-30			64	
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	84-74	40-30
0.5-30			74	30
0.15-0.5	CVP and current probe	Average / 9 kHz	74-64	30-20
0.5-30			64	20
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	40-30
0.5-30				30
0.15-0.5	Current Probe	Average / 9 kHz		30-20
0.5-30				20

3.2 Test Data: LAN10G\100M




No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	13.358	48.05	45.20	9.43	57.48	87.00	-29.52	54.63	74.00	-19.37
2	14.274	47.08	44.40	9.44	56.52	87.00	-30.48	53.84	74.00	-20.16
3	15.618	46.99	44.46	9.45	56.44	87.00	-30.56	53.91	74.00	-20.09
4	16.230	50.14	47.55	9.46	59.60	87.00	-27.40	57.01	74.00	-16.99
5	17.694	50.34	47.80	9.48	59.82	87.00	-27.18	57.28	74.00	-16.72
6	18.242	50.64	48.04	9.48	60.12	87.00	-26.88	57.52	74.00	-16.48
7	19.586	44.64	42.24	9.49	54.13	87.00	-32.87	51.73	74.00	-22.27

Note :

Margin = QP/AVG Emission – Limit
 Correct Factor = LISN Loss + Cable Loss
 The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.
 If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor
 A margin of -8dB means that the emission is 8dB below the limit

3.3 Test Data: LAN10G\10G



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.522	29.31	22.08	9.56	38.87	87.00	-48.13	31.64	74.00	-42.36
2	1.170	20.26	12.76	9.43	29.69	87.00	-57.31	22.19	74.00	-51.81
3	4.970	30.66	19.94	9.35	40.01	87.00	-46.99	29.29	74.00	-44.71
4	5.610	33.56	32.24	9.35	42.91	87.00	-44.09	41.59	74.00	-32.41
5	5.994	28.36	17.37	9.36	37.72	87.00	-49.28	26.73	74.00	-47.27
6	10.886	30.74	28.31	9.40	40.14	87.00	-46.86	37.71	74.00	-36.29

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.4 Test Data: LAN10G\1G



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	5.690	36.99	25.99	9.36	46.35	87.00	-40.65	35.35	74.00	-38.65
2	6.006	37.83	26.31	9.36	47.19	87.00	-39.81	35.67	74.00	-38.33
3	13.706	36.24	30.49	9.44	45.68	87.00	-41.32	39.93	74.00	-34.07
4	14.914	36.79	31.14	9.45	46.24	87.00	-40.76	40.59	74.00	-33.41
5	16.086	37.13	31.69	9.46	46.59	87.00	-40.41	41.15	74.00	-32.85
6	17.534	37.25	31.68	9.48	46.73	87.00	-40.27	41.16	74.00	-32.84
7	29.738	39.00	33.44	9.60	48.60	87.00	-38.40	43.04	74.00	-30.96

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.5 Test Data: LAN10G\2.5G Current



No.	Frequency (MHz)	QP_R (dBuA)	AVG_R (dBuA)	Correct Factor (dB)	QP Emission (dBuA)	QP Limit (dBuA)	QP Margin (dB)	AVG Emission (dBuA)	AVG Limit (dBuA)	AVG Margin (dB)
1	1.402	-11.1	-22.6	33.99	22.81	43.00	-20.19	11.38	30.00	-18.62
2	1.738	-14.5	-19.0	33.99	19.40	43.00	-23.60	14.97	30.00	-15.03
3	2.186	-11.5	-18.4	33.99	22.42	43.00	-20.58	15.58	30.00	-14.42
4	2.406	-12.1	-19.7	34.00	21.82	43.00	-21.18	14.26	30.00	-15.74
5	2.578	-10.6	-13.5	33.99	23.38	43.00	-19.62	20.48	30.00	-9.52
6	2.746	-6.11	-18.1	33.99	27.88	43.00	-15.12	15.81	30.00	-14.19
7	2.858	-6.03	-16.3	34.00	27.97	43.00	-15.03	17.69	30.00	-12.31
8	6.026	-17.6	-29.4	34.04	16.37	43.00	-26.63	4.56	30.00	-25.44

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.6 Test Data: LAN10G\2.5G Voltage




No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.162	45.66	37.50	20.67	66.33	96.36	-30.03	58.17	83.36	-25.19
2	0.282	45.23	42.11	20.67	65.90	91.76	-25.86	62.78	78.76	-15.98
3	0.562	42.02	33.95	20.66	62.68	87.00	-24.32	54.61	74.00	-19.39
4	1.458	44.36	33.26	20.65	65.01	87.00	-21.99	53.91	74.00	-20.09
5	2.798	40.28	30.04	20.64	60.92	87.00	-26.08	50.68	74.00	-23.32
6	6.010	39.83	26.44	20.63	60.46	87.00	-26.54	47.07	74.00	-26.93

Note :

Margin = QP/AVG Emission – Limit QP/AVG Emission = QP_R/AVG_R + Correct Factor
 Correct Factor = LISN Loss + Cable Loss A margin of -8dB means that the emission is 8dB below the limit
 The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.
 If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

3.7 Test Data: LAN1 2.5G\100M




No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	12.198	45.84	43.22	9.41	55.25	87.00	-31.75	52.63	74.00	-21.37
2	13.418	47.62	44.93	9.43	57.05	87.00	-29.95	54.36	74.00	-19.64
3	14.214	47.11	44.49	9.44	56.55	87.00	-30.45	53.93	74.00	-20.07
4	16.230	50.06	47.41	9.46	59.52	87.00	-27.48	56.87	74.00	-17.13
5	18.246	49.02	46.31	9.48	58.50	87.00	-28.50	55.79	74.00	-18.21
6	19.710	48.75	45.95	9.49	58.24	87.00	-28.76	55.44	74.00	-18.56

Note :

Margin = QP/AVG Emission – Limit
Correct Factor = LISN Loss + Cable Loss
The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.
If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor
A margin of -8dB means that the emission is 8dB below the limit

3.8 Test Data: LAN1 2.5G\1G



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	5.966	36.34	25.79	9.36	45.70	87.00	-41.30	35.15	74.00	-38.85
2	12.002	34.98	29.53	9.41	44.39	87.00	-42.61	38.94	74.00	-35.06
3	14.414	36.47	30.99	9.44	45.91	87.00	-41.09	40.43	74.00	-33.57
4	16.574	37.21	31.75	9.46	46.67	87.00	-40.33	41.21	74.00	-32.79
5	20.494	36.54	31.10	9.49	46.03	87.00	-40.97	40.59	74.00	-33.41
6	29.970	37.87	32.36	9.60	47.47	87.00	-39.53	41.96	74.00	-32.04

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.9 Test Data: LAN1 2.5G\2.5G Current



No.	Frequency (MHz)	QP_R (dBuA)	AVG_R (dBuA)	Correct Factor (dB)	QP Emission (dBuA)	QP Limit (dBuA)	QP Margin (dB)	AVG Emission (dBuA)	AVG Limit (dBuA)	AVG Margin (dB)
1	1.398	-8.06	-20.8	33.99	25.93	43.00	-17.07	13.10	30.00	-16.90
2	1.850	-11.0	-15.6	34.00	22.91	43.00	-20.09	18.34	30.00	-11.66
3	2.186	-7.96	-13.2	33.99	26.03	43.00	-16.97	20.75	30.00	-9.25
4	2.242	-7.88	-14.6	33.99	26.11	43.00	-16.89	19.31	30.00	-10.69
5	2.466	-4.97	-11.2	34.00	29.03	43.00	-13.97	22.77	30.00	-7.23
6	2.578	-6.44	-10.4	33.99	27.55	43.00	-15.45	23.50	30.00	-6.50
7	2.690	-4.88	-11.0	33.99	29.11	43.00	-13.89	22.90	30.00	-7.10
8	2.802	-2.76	-13.8	34.00	31.24	43.00	-11.76	20.13	30.00	-9.87

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.10 Test Data: LAN1 2.5G\2.5G Voltage



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.162	46.14	40.02	20.67	66.81	96.36	-29.55	60.69	83.36	-22.67
2	0.506	42.87	38.86	20.66	63.53	87.00	-23.47	59.52	74.00	-14.48
3	0.786	43.41	40.06	20.65	64.06	87.00	-22.94	60.71	74.00	-13.29
4	0.898	43.34	38.52	20.65	63.99	87.00	-23.01	59.17	74.00	-14.83
5	1.402	49.12	35.97	20.65	69.77	87.00	-17.23	56.62	74.00	-17.38
6	1.454	47.65	35.73	20.65	68.30	87.00	-18.70	56.38	74.00	-17.62
7	1.850	41.61	36.96	20.64	62.25	87.00	-24.75	57.60	74.00	-16.40
8	2.858	45.02	33.32	20.64	65.66	87.00	-21.34	53.96	74.00	-20.04

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.11 Test Data: LAN2 2.5G\100M



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	12.198	46.14	43.45	9.41	55.55	87.00	-31.45	52.86	74.00	-21.14
2	13.418	47.73	45.06	9.43	57.16	87.00	-29.84	54.49	74.00	-19.51
3	14.274	46.93	44.17	9.44	56.37	87.00	-30.63	53.61	74.00	-20.39
4	16.230	49.92	47.04	9.46	59.38	87.00	-27.62	56.50	74.00	-17.50
5	18.242	50.30	47.48	9.48	59.78	87.00	-27.22	56.96	74.00	-17.04
6	19.710	48.39	45.48	9.49	57.88	87.00	-29.12	54.97	74.00	-19.03

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.12 Test Data: LAN2 2.5G\1G



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	14.378	36.90	31.25	9.44	46.34	87.00	-40.66	40.69	74.00	-33.31
2	15.114	37.10	31.57	9.45	46.55	87.00	-40.45	41.02	74.00	-32.98
3	16.858	37.42	31.87	9.46	46.88	87.00	-40.12	41.33	74.00	-32.67
4	19.194	37.23	31.82	9.49	46.72	87.00	-40.28	41.31	74.00	-32.69
5	21.254	36.00	30.48	9.50	45.50	87.00	-41.50	39.98	74.00	-34.02
6	29.186	37.41	31.98	9.59	47.00	87.00	-40.00	41.57	74.00	-32.43

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.13 Test Data: LAN2 2.5G\2.5G Current



No.	Frequency (MHz)	QP_R (dBuA)	AVG_R (dBuA)	Correct Factor (dB)	QP Emission (dBuA)	QP Limit (dBuA)	QP Margin (dB)	AVG Emission (dBuA)	AVG Limit (dBuA)	AVG Margin (dB)
1	1.402	-4.94	-17.8	33.99	29.05	43.00	-13.95	16.14	30.00	-13.86
2	1.454	-6.62	-17.0	33.99	27.37	43.00	-15.63	16.99	30.00	-13.01
3	1.514	-7.61	-16.2	34.00	26.39	43.00	-16.61	17.78	30.00	-12.22
4	1.570	-4.94	-13.3	34.00	29.06	43.00	-13.94	20.67	30.00	-9.33
5	1.622	-8.54	-18.1	34.00	25.46	43.00	-17.54	15.87	30.00	-14.13
6	1.738	-7.47	-11.7	33.99	26.52	43.00	-16.48	22.27	30.00	-7.73
7	1.794	-6.81	-13.1	33.99	27.18	43.00	-15.82	20.84	30.00	-9.16
8	1.850	-5.24	-10.3	34.00	28.76	43.00	-14.24	23.62	30.00	-6.38
9	1.962	-4.79	-12.5	33.99	29.20	43.00	-13.80	21.47	30.00	-8.53
10	2.018	-2.04	-10.7	33.99	31.95	43.00	-11.05	23.23	30.00	-6.77
11	2.074	-4.18	-8.41	33.99	29.81	43.00	-13.19	25.58	30.00	-4.42
12	2.130	-5.52	-12.4	33.99	28.47	43.00	-14.53	21.55	30.00	-8.45
13	2.242	-6.80	-12.9	33.99	27.19	43.00	-15.81	21.06	30.00	-8.94
14	2.466	-6.13	-11.4	34.00	27.87	43.00	-15.13	22.60	30.00	-7.40
15	2.578	-5.56	-9.81	33.99	28.43	43.00	-14.57	24.18	30.00	-5.82
16	2.746	-3.69	-13.9	33.99	30.30	43.00	-12.70	20.06	30.00	-9.94
17	2.858	-2.79	-15.0	34.00	31.21	43.00	-11.79	18.99	30.00	-11.01

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.14 Test Data: LAN2 2.5G\2.5G Voltage



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.450	43.76	39.59	20.66	64.42	87.88	-23.46	60.25	74.88	-14.63
2	0.562	42.20	39.38	20.66	62.86	87.00	-24.14	60.04	74.00	-13.96
3	0.670	40.30	35.83	20.65	60.95	87.00	-26.05	56.48	74.00	-17.52
4	1.402	45.99	32.83	20.65	66.64	87.00	-20.36	53.48	74.00	-20.52
5	1.458	45.17	34.86	20.65	65.82	87.00	-21.18	55.51	74.00	-18.49
6	2.018	41.24	32.06	20.64	61.88	87.00	-25.12	52.70	74.00	-21.30
7	6.218	41.04	33.08	20.63	61.67	87.00	-25.33	53.71	74.00	-20.29
8	6.666	42.51	38.28	20.63	63.14	87.00	-23.86	58.91	74.00	-15.09

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.15 Test Data: LAN3 2.5G\100M



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	13.418	47.84	45.08	9.43	57.27	87.00	-29.73	54.51	74.00	-19.49
2	14.214	47.19	44.33	9.44	56.63	87.00	-30.37	53.77	74.00	-20.23
3	15.618	46.75	43.87	9.45	56.20	87.00	-30.80	53.32	74.00	-20.68
4	16.230	49.92	46.98	9.46	59.38	87.00	-27.62	56.44	74.00	-17.56
5	17.694	50.20	47.29	9.48	59.68	87.00	-27.32	56.77	74.00	-17.23
6	18.242	50.42	47.61	9.48	59.90	87.00	-27.10	57.09	74.00	-16.91
7	19.710	48.37	45.44	9.49	57.86	87.00	-29.14	54.93	74.00	-19.07

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.16 Test Data: LAN3 2.5G\1G



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	13.102	36.55	30.92	9.43	45.98	87.00	-41.02	40.35	74.00	-33.65
2	14.802	37.05	31.56	9.45	46.50	87.00	-40.50	41.01	74.00	-32.99
3	15.974	37.59	32.01	9.46	47.05	87.00	-39.95	41.47	74.00	-32.53
4	18.182	37.60	32.03	9.48	47.08	87.00	-39.92	41.51	74.00	-32.49
5	20.230	36.65	31.27	9.49	46.14	87.00	-40.86	40.76	74.00	-33.24
6	29.334	37.93	32.42	9.59	47.52	87.00	-39.48	42.01	74.00	-31.99

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.17 Test Data: LAN3 2.5G\2.5G Current



No.	Frequency (MHz)	QP_R (dBuA)	AVG_R (dBuA)	Correct Factor (dB)	QP Emission (dBuA)	QP Limit (dBuA)	QP Margin (dB)	AVG Emission (dBuA)	AVG Limit (dBuA)	AVG Margin (dB)
1	1.346	-10.9	-19.1	34.00	23.10	43.00	-19.90	14.87	30.00	-15.13
2	1.458	-7.43	-18.7	33.99	26.56	43.00	-16.44	15.29	30.00	-14.71
3	1.626	-8.20	-15.7	33.99	25.79	43.00	-17.21	18.20	30.00	-11.80
4	1.682	-9.17	-13.4	33.99	24.82	43.00	-18.18	20.58	30.00	-9.42
5	1.850	-9.20	-13.7	34.00	24.80	43.00	-18.20	20.26	30.00	-9.74
6	1.962	-7.01	-12.7	33.99	26.98	43.00	-16.02	21.28	30.00	-8.72
7	2.074	-8.47	-14.0	33.99	25.52	43.00	-17.48	19.99	30.00	-10.01
8	2.186	-8.08	-12.2	33.99	25.91	43.00	-17.09	21.79	30.00	-8.21
9	2.298	-7.63	-12.3	34.00	26.37	43.00	-16.63	21.62	30.00	-8.38
10	2.410	-6.18	-10.5	34.00	27.82	43.00	-15.18	23.47	30.00	-6.53
11	2.690	-9.03	-14.5	33.99	24.96	43.00	-18.04	19.48	30.00	-10.52
12	2.802	-5.42	-11.3	34.00	28.58	43.00	-14.42	22.66	30.00	-7.34
13	2.914	-5.60	-14.2	34.00	28.40	43.00	-14.60	19.78	30.00	-10.22
14	3.138	-8.16	-14.1	34.00	25.84	43.00	-17.16	19.81	30.00	-10.19

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit

3.18 Test Data: LAN3 2.5G\2.5G Voltage



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.282	47.98	44.76	20.67	68.65	91.76	-23.11	65.43	78.76	-13.33
2	0.394	43.51	39.81	20.66	64.17	88.98	-24.81	60.47	75.98	-15.51
3	0.674	42.85	38.54	20.65	63.50	87.00	-23.50	59.19	74.00	-14.81
4	0.730	42.32	35.66	20.65	62.97	87.00	-24.03	56.31	74.00	-17.69
5	0.898	45.34	41.05	20.65	65.99	87.00	-21.01	61.70	74.00	-12.30
6	1.398	43.80	33.76	20.65	64.45	87.00	-22.55	54.41	74.00	-19.59

Note :

Margin = QP/AVG Emission – Limit

Correct Factor = LISN Loss + Cable Loss

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

QP/AVG Emission = QP_R/AVG_R + Correct Factor

A margin of -8dB means that the emission is 8dB below the limit




3.19 Test Setup Photo

Refer to the Setup Photos for Power Main Port Conducted Emissions

4. Radiated Disturbance Emissions

4.1 Test Setup and Procedure

4.1.1 Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.

Frequency (GHz)	E-plane	H-plane	$\theta_{3\text{dB}}(\text{min})$	d= 3 m
				w (m)
1	88°	147°	88°	5.79
2	68°	119°	68°	4.04
3	73°	92°	73°	4.44
4	70°	89°	70°	4.20
5	55°	60°	55°	3.12
6	63°	62°	62°	3.60

4.1.2 Test Procedure

The radiated emissions test will then be repeated on the open site or chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter open field sites or 10 meter chamber. Desktop EUT are set up on a FRP stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 6 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to EN 55032 requirements.

The highest internal source of an EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes.

If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz.

If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.

If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.

If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.

4.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1 GHz to 6 GHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

4.2 Limit

Radiated emissions at frequencies up to 1 GHz for Class_A equipment:

Frequency range MHz	Measurement		Class_A limits dB(μ V/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	40
230-1000			47
30-230	3		50
230-1000			57

Radiated emissions at frequencies above 1 GHz for Class_A equipment:

Frequency range MHz	Measurement		Class_A limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	56
3000-6000			60
1000-3000		Peak / 1MHz	76
3000-6000			80

Radiated emissions at frequencies up to 1 GHz for Class_B equipment:

Frequency range MHz	Measurement		Class_B limits dB(μV/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	30
230-1000			37
30-230	3		40
230-1000			47

Radiated emissions at frequencies above 1 GHz for Class_B equipment:


Frequency range MHz	Measurement		Class_B limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	50
3000-6000			54
1000-3000		Peak / 1MHz	70
3000-6000			74

Radiated emissions from FM receivers:

Frequency range MHz	Measurement		Class_B limits dB(μV/m)	
	Distance m	Detector type / bandwidth	Fundamental	Harmonics
			OATS/SAC	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	50	42
230-300				42
300-1000				46
30-230	3		60	52
230-300				52
300-1000				56

4.3 Radiation Test Data: Configuration 1

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	125.06	44.34	-18.03	26.31	40.00	-13.69	308	262	peak
2	266.68	45.21	-15.48	29.73	47.00	-17.27	310	138	peak
3	321.97	46.82	-13.30	33.52	47.00	-13.48	106	85	peak
4	527.61	40.90	-8.33	32.57	47.00	-14.43	151	194	peak
5	625.58	37.06	-5.93	31.13	47.00	-15.87	317	53	peak
6	800.18	41.51	-3.22	38.29	47.00	-8.71	255	340	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.




Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-4071718

Radiated Emission Measurement

Date: 2019/12/31

Operator: Stanley
Temperature: 26 °C
Humidity: 60 %



Site : Chamber 14

Polarization: *Horizontal*

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1600.00	67.69	-16.09	51.60	76.00	-24.40	257	180	peak
2	2400.00	62.46	-12.28	50.18	76.00	-25.82	100	180	peak
3	3200.00	63.83	-10.66	53.17	80.00	-26.83	200	180	peak
4	4000.00	61.19	-10.12	51.07	80.00	-28.93	107	180	peak
5	5000.00	61.26	-9.29	51.97	80.00	-28.03	139	180	peak
6	5999.99	60.73	-7.81	52.92	60.00	-7.08	103	181	AVG
7	6000.00	71.47	-7.81	63.66	80.00	-16.34	104	180	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	42.61	52.57	-17.28	35.29	40.00	-4.71	144	313	peak
2	297.72	46.65	-14.18	32.47	47.00	-14.53	101	117	peak
3	321.97	47.92	-13.30	34.62	47.00	-12.38	337	287	peak
4	527.61	41.62	-8.33	33.29	47.00	-13.71	369	260	peak
5	625.58	35.96	-5.93	30.03	47.00	-16.97	192	339	peak
6	800.18	39.55	-3.22	36.33	47.00	-10.67	230	37	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.




Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-4071718

Radiated Emission Measurement

Date: 2019/12/31

Operator: Stanley
Temperature: 26 °C
Humidity: 60 %



Site : Chamber 14

Polarization: Vertical

Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor (dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1600.00	65.10	-16.09	49.01	76.00	-26.99	100	180	peak
2	2399.99	59.07	-12.28	46.79	56.00	-9.21	101	181	AVG
3	2400.00	65.83	-12.28	53.55	76.00	-22.45	100	180	peak
4	3200.00	63.32	-10.66	52.66	80.00	-27.34	105	180	peak
5	4000.00	59.23	-10.12	49.11	80.00	-30.89	194	180	peak
6	4990.00	59.97	-9.29	50.68	80.00	-29.32	100	180	peak
7	5999.99	63.70	-7.81	55.89	60.00	-4.11	167	177	AVG
8	6000.00	72.30	-7.81	64.49	80.00	-15.51	166	180	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters


Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

4.4 Test Setup Photo


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)




Back View (above 1GHz)



5. Voltage Disturbance Emissions at Antenna Terminals

5.1 Test Setup and Procedure

5.1.1 Test Setup



5.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dBuV at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

5.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

5.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.


Table clause	Frequency range MHz	Detector type/ bandwidth	Class B limits dB(μV) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies ≤1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300	For frequencies ≥1 GHz	46	54	50	See c)
	300 – 1 000				52	
A12.4	30 – 300	Peak/ 1 MHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	
a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.						
b) Tuner units (not the LNB) for satellite signal reception.						
c) Frequency modulation audio receivers and PC tuner cards.						
d) Frequency modulation car radios.						
e) Applicable to EUTs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.						

****Remarks: It is not necessary to be tested on this item.**

6. Differential Voltage Emissions

6.1 Test Setup and Procedure

6.1.1 Test Setup



6.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dBuV at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

6.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

6.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.



Table clause	Frequency range MHz	Detector type/ bandwidth	Class B limits dB(μV) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies ≤1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300		46	54	50	See c)
	300 – 1 000	52				
A12.4	30 – 300	For frequencies ≥1 GHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	
a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.						
b) Tuner units (not the LNB) for satellite signal reception.						
c) Frequency modulation audio receivers and PC tuner cards.						
d) Frequency modulation car radios.						
e) Applicable to EUTs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.						

****Remarks: It is not necessary to be tested on this item.**

7. Outdoor units of home satellite receiving systems

7.1 Test Setup and Procedure

7.1.1 Test Setup

	
Description of $\pm 7^\circ$ of the main beam axis of the EUT	Measurement arrangements of transmit antenna for the wanted signal

7.1.2 Test Procedure

The input signal shall be adjusted to get the maximum rated output level from the EUT. For the measurement in the frequency range from 30 MHz to 18 GHz the input signal shall be adjusted so that the output frequency is within this frequency range. For the measurement in the frequency range above 1 GHz, the frequency of the input signal shall be adjusted in such a way that the EUT is measured, as a minimum, at the lowest, middle and highest rated output frequency within the measured frequency range.

7.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1000MHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

7.1.4 Limit

Table Clause	Frequency Range MHz	Measurement			Class B Limits	Applicable to
		Facility (see Table A.1)	Distance m	Detector type / Bandwidth		
A7.1	30 to 1 000	SAC / OATS / FAR	See Table A.4	Quasi Peak / 120 kHz	See Table A.4	
A7.2	1 000 to 2 500	FSOATS	3	Average / 1 MHz	50 dB(μV/m)	LO leakage and spurious radiated emissions from the EUT, in the region outside ±7° of the main beam axis. See Figure H.1
	2 500 to 18 000				64 dB(μV/m)	
A7.3	1 000 to 18 000	FSOATS	3	Average / 1 MHz	37 dB(μV/m)	LO leakage from the EUT, in the region within ±7° of the main beam axis. See Figure H.1
A7.4	1 000 to 18 000	Conducted (Clause H.4)	n/a	Average / 1 MHz	30 dBpW	
For details of the EUT configuration, see Annex H.						
For radiated emissions measurements at frequencies up to 1 GHz, the requirements defined in Table A.4 shall be satisfied.						
Apply the appropriate limits across the entire frequency range.						
Apply the limits defined in table Clause A7.1 and A7.2. Also apply the limits defined in either table Clause A7.3 or A7.4.						

****Remarks: It is not necessary to be tested on this item.**

8. Electrostatic discharge (ESD) immunity

8.1 Test Specification and Setup

8.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-2/ IEC 61000-4-2 (details referred to Sec 1.2)
Test Level:	Air +/- 2 kV, +/- 4 kV, +/- 8 kV Contact +/- 4 kV
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S7
Temperature:	22°C
Humidity:	40%

Selected Test Point


Air: discharges were applied to slots, aperture or insulating surfaces. 10 single air discharges were applied to each selected points.

Contact: Total 200 discharges minimum were to the selected contact points.

Indirect Contact Points: 25 discharges were applied to center of one edge of VCP and each EUT side of HCP with 10 cm away from EUT.

8.1.2 Test Setup

EUT is 1m from the wall and other metallic structure. When Battery test mode is needed, a cable with one 470KΩ resistor at two rare ends is connected from metallic part of EUT and screwed to HCP.



8.1.3 Test Result

Performance of EUT complies with the given specification


8.2 Test Point

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.


Figure 1: Test Point Assignments Discharge:



Figure 2: Test Point Assignments Discharge:



8.3 Test Setup Photo



9. Radio-Frequency, Electromagnetic Field immunity


9.1 Test Specification and Setup

9.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-3/ IEC 61000-4-3 (details referred to Sec 1.2)
Test Level:	3 V/m
Modulation:	AM 1kHz 80%
Frequency range:	80 MHz~1 GHz
Frequency Step:	1% of last step frequency
Dwell time:	3s
Polarization:	Vertical and Horizontal
EUT Azimuth Angle	<input checked="" type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input checked="" type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S8
Temperature:	22°C
Humidity:	52%

9.1.2 Test Setup

The field sensor is placed at one calibration grid point to check the intensity of the established fields on both polarizations. EUT is adjusted to have each side of EUT face coincident with the calibration plane. A CCD camera and speakers are used to monitor the condition of EUT for the performance judgment.



9.1.3 Test Result

Performance of EUT complies with the given specification

9.2 Test Setup Photo



10. Electrical Fast transients/burst immunity

10.1 Test Specification and Setup

10.1.1 Test Specification

Port:	AC mains; Twisted Pair LAN Port
Basic Standard:	EN 61000-4-4/ IEC 61000-4-4 (details referred to Sec 1.2)
Test Level:	AC Power Port: +/- 1 Kv (I/O Cables): +/- 0.5 kV
Rise Time:	5ns
Hold Time:	50ns
Burst Period:	300ms
Repetition Frequency:	5kHz
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S9
Temperature:	21 °C
Humidity:	51%

Test Procedure



The EUT was setup on a nonconductive table 0.1 m above a reference ground plane.

Test Points	Polarity	Result	Comment
Line	+	N	60 sec
	-	N	60 sec
Neutral	+	N	60 sec
	-	N	60 sec
Ground	+	N	60 sec
	-	N	60 sec
Line to Neutral	+	N	60 sec
	-	N	60 sec
Line to Ground	+	N	60 sec
	-	N	60 sec
Neutral to Ground	+	N	60 sec
	-	N	60 sec
Line to Neutral to Ground	+	N	60 sec
	-	N	60 sec
Capacitive coupling clamp	+	N	60 sec
	-	N	60 sec

Note: 'N' means normal, the EUT function is correct during the test.

10.1.2 Test Setup

EUT is at least 50cm from the conductive structure.



10.1.3 Test Result

Performance of EUT complies with the given specification

10.2 Test Setup Photo




11. Surge Immunity

11.1 Test Specification and Setup

11.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-5/ IEC 61000-4-5 (details referred to Sec 1.2)
Test Level:	Line to Line: +/- 0.5 kV, +/- 1 kV Line to Earth: +/- 0.5 kV, +/- 1 kV, +/- 2kV
Rise Time:	1.2us
Hold Time:	50us
Repetition Rate:	30 seconds
Angle:	<input checked="" type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input checked="" type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S10
Temperature:	23°C
Humidity:	53%

11.1.2 Test Setup



11.1.3 Test Result

Performance of EUT complies with the given specification

11.2 Test Setup Photo




12. Immunity to Conductive Disturbance

12.1 Test Specification and Setup

12.1.1 Test Specification

Port:	AC mains; Twisted Pair LAN Port
Basic Standard:	EN 61000-4-6/ IEC 61000-4-6 (details referred to Sec 1.2)
Test Level:	3 V
Modulation:	AM 1kHz 80%
Frequency range:	0.15 MHz - 80MHz
Frequency Step:	1% of last Frequency
Dwell time:	3s
Criteria:	A
CDN Type:	CDN M2+M3, CDN T4, CDN T8, EM Clamp
Test Procedure	refer to ISL QA -T4-E-S11
Temperature:	22°C
Humidity:	53%

12.1.2 Test Setup



12.1.3 Test Result

Performance of EUT complies with the given specification

12.2 Test Setup Photo




13. Power Frequency Magnetic Field immunity

13.1 Test Specification and Setup

13.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-8/ IEC 61000-4-8 (details referred to Sec 1.2)
Test Level:	1A/m
Polarization:	X, Y, Z
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S12
Temperature:	21°C
Humidity:	53%

13.1.2 Test Setup



13.1.3 Test Result

Performance of EUT complies with the given specification

13.2 Test Setup Photo




14. Voltage Dips, Short Interruption and Voltage Variation immunity

14.1 Test Specification and Setup

14.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-11/ IEC 61000-4-11 (details referred to Sec 1.2)
Test Level: Criteria:	>95% in 0.5 period B
Test Level: Criteria:	30% in 25 period C
Test Level: Criteria:	>95% in 250 period C
Phase:	0°; 180°
Test intervals:	3 times with 10s each
Test Procedure	refer to ISL QA -T4-E-S13
Temperature:	23°C
Humidity:	51%

14.1.2 Test Setup



14.1.3 Test Result

Performance of EUT complies with the given specification

14.2 Test Setup Photo



15. Harmonics

15.1 Test Specification and Setup

15.1.1 Test Specification


Port:	AC mains
Active Input Power:	<75W
Basic Standard:	EN 61000-3-2/IEC 61000-3-2 (details referred to Sec 1.2)
Test Duration:	2.5min
Class:	A
Test Procedure	refer to ISL QA -T4-E-S14
Temperature:	22°C
Humidity:	53%

Test Procedure

The EUT is supplied in series with shunts or current transformers from a source having the same nominal voltage and frequency as the rated supply voltage and frequency of the EUT. The EUT is configured to its rated current with additional resistive load when the testing is performed.

Equipment having more than one rated voltage shall be tested at the rated voltage producing the highest harmonics as compared with the limits.

15.1.2 Test Setup



15.1.3 Limit

Limits of Class A Harmonics Currents

Harmonics Order n	Maximum Permissible harmonic current A	Harmonics Order n	Maximum Permissible harmonic current A
Odd harmonics		Even harmonics	
3	2.30	2	1.08
5	1.14	4	0.43
7	0.77	6	0.30
9	0.40	$8 \leq n \leq 40$	$0.23 * 8/n$
11	0.33		
13	0.21		
$15 \leq n \leq 39$	$0.15 * 15/n$		

15.1.4 Test Result

Active input power under 75W, no limit apply, declare compliance

16. Voltage Fluctuations

16.1 Test Specification and Setup


16.1.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-3-3/IEC61000-3-3 (details referred to Sec 1.2)
Test Procedure	refer to ISL QA -T4-E-S14
Observation period:	For Pst 10min
	For Plt 2 hours
Temperature:	22°C
Humidity:	53%

Test Procedure

The EUT is supplied in series with reference impedance from a power source with the voltage and frequency as the nominal supply voltage and frequency of the EUT.

16.1.2 Test Setup



16.1.3 Test Result

Performance of EUT complies with the given specification.

16.2 Test Data


Flicker Test Summary per EN/IEC61000-3-3 Ed. 3.0 (2013) (Run time)

Test duration (min): 10 Data file name: CTSMXL_F-001794.cts_data
Comment: Comment
Customer: Customer information


Test Result: Pass Status: Test Completed

Pst_i and limit line

European Limits



Plt and limit line



Parameter values recorded during the test:

Vrms at the end of test (Volt):	229.62	Test limit (mS):	500.0	Pass
T-max (mS):	0.0	Test limit (%):	3.30	Pass
Highest dc (%):	0.00	Test limit (%):	4.00	Pass
Highest dmax (%):	-0.05	Test limit:	1.000	Pass
Highest Pst (10 min. period):	0.064	Test limit:	0.650	Pass
Highest Plt (2 hr. period):	0.028			

16.3 Test Setup Photo



17. Appendix

17.1 Appendix A: Test Equipment

17.1.1 Test Equipment List

Location Con02	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 02	LISN 26	R&S	ENV216	102378	11/21/2019	11/21/2020
Conduction 02	LISN 21	R&S	ENV216	101476	07/31/2019	07/31/2020
Conduction 02	Conduction 02-1 Cable	WOKEN	CFD 300-NL	Conduction 02 -1	09/11/2019	09/11/2020
Conduction 02	EMI Receiver 14	ROHDE& SCHWARZ	ESCI	101034	05/31/2019	05/31/2020
Conduction 02	ISN T8 CAT6A_01	Schwarzbeck	NTFM 8158	8158 0123	11/01/2019	11/01/2020
Conduction 02	ISN T8 10	Teseq GmbH	ISN T800	42773	08/02/2019	08/02/2020
Conduction 02	Capacitive Voltage Probe	FCC	F-CVP-1	68	02/19/2019	02/19/2020
Conduction 02	Current Probe	SCHAFFNER	SMZ 11	18030	02/19/2019	02/19/2020

Location Chamber02	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Radiation (Chamber02)	BILOG Antenna 17	Schwarzbeck	Schwarzbeck VULB 9168+EMCI-N -6-05	645	03/06/2019	03/06/2020
Radiation (Chamber02)	Preamplifier 25	EMCI	EMC9135	980295	02/27/2019	02/27/2020
Radiation (Chamber02)	Coaxial Cable Chmb 02-10M-02	EMC	RG214U	Chmb 02-10M-02	09/16/2019	09/16/2020
Radiation (Chamber02)	EMI Receiver 12	ROHDE & SCHWARZ	ESCI	100804	08/30/2019	08/30/2020

Location Chmb14	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Rad. Above 1GHz	Spectrum Analyzer 25	R&S	FSV 40	101499	11/01/2019	11/01/2020
Rad. Above 1GHz	Horn Antenna 13	ETS-Lindgren	3117	0161229	09/09/2019	09/09/2020
Rad. Above 1GHz	Preamplifier 20	EMC INSTRUMENT	EMC051845/E MCI-S-18-06	980084/AT-S 18001	03/21/2019	03/21/2020
Rad. Above 1GHz	Microwave Cable 35	WOKEN	WCBA-WCA0 4NM.SM6	Chamber 14-1	01/31/2019	01/31/2020
Rad. Above 1GHz	Microwave Cable 36	WOKEN	WCBA-WCA0 4NM.SM0.8	Chamber 14-2	01/31/2019	01/31/2020

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
EN61K-4-2	ESD Gun 12	EM TEST	Dito	P1650188689	05/07/2019	05/07/2020
EN61K-4-3	Broadband Log-Periodic Antenna	AR	AT1080	310698	N/A	N/A
EN61K-4-3	Horn Antenna RF-01	AR	ATS700M11 G	0335864	N/A	N/A
EN61K-4-3	Amplifier 80Mz~1GHz 250W	AR	250W1000A	312494	N/A	N/A
EN61K-4-3	Amplifier 800MHz~4.2GHz 50W	AR	50S1G4M1	312762	N/A	N/A
EN61K-4-3	Amplifier 4.0~8.0GHz 35W	AR	35S4G8AM1	0335752	N/A	N/A
EN61K-4-3	Broadband Coupler 80M~1GHz	Amplifier Research	DC6180A	0341805	N/A	N/A
EN61K-4-3	Coaxial Cable	INSULATED	NPS-4806-23 60-NP3	108599.003.01.03	N/A	N/A
EN61K-4-3	Broadband Coupler 0.8G~4.26GHz	AR	DC7144A	0335226	N/A	N/A
EN61K-4-3	Broadband Coupler 4G~8GHz	AR	DC7350A	0335817	N/A	N/A
EN61K-4-3	Signal Generator 07	ROHDE& SCHWARZ	SMB100A	107780	12/04/2019	12/04/2020
EN61K-4-4 EN61K-4-5	EFT and SURGE Test System	EM TEST	UCS-500 M6B	V0728102674	02/14/2019	02/14/2020
EN61K-4-4	Capacitive Coupling Clamp	EM TEST	HFK	0907-106	02/14/2019	02/14/2020
EN61K-4-6	CDN M2+M3 04	TESEQ	CDN M016	43257	09/10/2019	09/10/2020
EN61K-4-6	CDN T4 06	FCC Inc.	FCC-801-T4	02068	06/24/2019	06/24/2020
EN61K-4-6	CDN T8-10_2	Teseq GmbH	CDN T8 10	41241	03/26/2019	03/26/2020
EN61K-4-6	Coaxial Cable 4-6 02-1			4-6 02-1	N/A	N/A
EN61K-4-6	Conducted Immunity Test System 02	Frankonia	CIT-10-75-D C	126B1301/2014	03/25/2019	03/25/2020
EN61K-4-6	EM-Clamp	Schaffner	KEMZ-801	19215	11/22/2019	11/22/2020
EN61K-4-8	Magnetic Field Immunity Loop	FCC	F-1000-4-8-L-1M	01037	05/27/2019	06/05/2020
EN61K-4-8	Magnetic Field Test Generator	FCC	F-1000-4-8-G -125A	01038	05/27/2019	06/05/2020
EN61K-4-11	Voltage Dip and UP Simulator 01	NoiseKen	VDS-2002	VDS1750439	09/25/2019	09/25/2020
EN61K-3-2/3, EN61K-3-11-1 2	(Harmonic/Flicker) MX Series CTSH Compliance Test System	California Instruments	MX60T04GH 10400	72793	08/05/2019	08/05/2020

PS: N/A => The equipment does not need calibration.

****Software for Controlling Spectrum/Receiver and Calculating Test Data**

Test Item	Filename	Version
EN61000-3-2	California Instruments	CTSMXL V2.19.0
EN61000-3-3	California Instruments	CTSMXL V2.19.0
EN61000-4-2	N/A	2.0
EN61000-4-3	i2	4.130102k
EN61000-4-4	EMC TEST	4.10
EN61000-4-5	EMC TEST	4.10
EN61000-4-6	FRANKONIA CD-LAB	V5.221
EN61000-4-8	N/A	
EN61000-4-11	NOISE KEN	2.0

Site	Filename	Version	Issue Date
Conduction/Radiation	EZ EMC	ISL-03A2	3/6/2013

17.2 Appendix B: Uncertainty of Measurement

The laboratory measurement uncertainty accordance with refers to CISPR 16-4-2. If U_{lab} is less than or equal to U_{cisp} in Table 1, then the test report may either state the value of U_{lab} or state that U_{lab} is less than U_{cisp} .

The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 02>

AMN: $\pm 2.94\text{dB}$

ISN T8: $\pm 3.09\text{dB}$

CVP: $\pm 3.62\text{dB}$

CP: $\pm 2.88\text{dB}$

<Chamber 02 (10M)>

Horizontal

30MHz~200MHz: $\pm 4.52\text{dB}$

200MHz~1000MHz: $\pm 4.42\text{dB}$

Vertical

30MHz~200MHz: $\pm 4.51\text{dB}$

200MHz~1000MHz: $\pm 4.70\text{dB}$

<Chamber 14 (3M)>

1GHz~6GHz: $\pm 4.93\text{dB}$

<Immunity 02>

Test item	Uncertainty	Test item	Uncertainty
EN 61000-4-2 (ESD)		EN 61000-4-6 (CS)	
Rise time tr	$\leq 9.81\%$	CDN	$\pm 1.74\text{dB}$
Peak current Ip	$\leq 5.54\%$	EM Clamp	$\pm 3.36\text{dB}$
current at 30 ns	$\leq 5.55\%$	EN 61000-4-8 (Magnetic)	$\pm 6.53\%$
current at 60 ns	$\leq 5.55\%$	EN 61000-4-11 (Dips)	$\pm 2.41\%$
EN 61000-4-3 (RS)	$\pm 1.89\text{dB}$	EN 61000-3-2 (Harmonics)	$\pm 1.29\%$
EN 61000-4-4 (EFT)		EN 61000-3-3 (Fluctuations and Flicker)	$\pm 6.8\%$
voltage rise time (tr)	$\pm 5.1\%$		
peak voltage value (VP)	$\pm 6.39\%$		
voltage pulse width (tw)	$\pm 5.0\%$		
EN 61000-4-5 (Surge)			
open-circuit voltage front time	$\pm 13.5\%$		
open-circuit voltage peak value	$\pm 6.6\%$		
open-circuit voltage duration (Td)	$53.33\mu\text{s}$		

17.3 Appendix C: Photographs of EUT

Please refer to the File of **ISL-20LE044P**